

FALCON HOMES

SINGLE FAMILY HOMES

STANDARD FFATURES

FOUNDATION

- Footings: 8" x 18", 20 MPA concrete
- Basement Floor: 3.5" concrete, 25 MPA on 6" of sand
- 8' high Basement ceiling
- 20 MPA Concrete used for all footings and foundation walls
- Poured standard brushed concrete sidewalk & driveway
- Steel angle brackets mounted directly to foundation for exterior sidewalk support (where applicable)
- Corrugated weeping tile around foundation perimeter
- Smoothed/polished concrete floors in basement

STRUCTURE

- Engineered I-joist floor system
- Sub floor: 23/32" tongue & groove O.S.B. glued & nailed. Proboard installed under lino area 3/8"
- Exterior walls: 2" X 6" studs @ 24" O.C. provide greater insulation value
- Interior walls: 2" X 4" studs @ 24" O.C.

- Basement frost walls: 2" X 4" studs @ 24" O.C.
- Roof Truss: engineer approved 24" O.C.
- Roof Sheathing: 7/16" O.S.B sheathing with H-clip
- Two-storey ceiling height: 9' main and 8' upper floor
- Bugalow/Bi-level ceiling height: 9' Flat main or 8' with vault as per plans.

EXTERIOR WINDOWS, DOORS & FINISHINGS

WINDOWS

- · Oversized windows
- Basement windows sized and located for future basement development
- Energy star, Low E, argon filled triple pane windows

EXTERIOR DOORS

• Insulated Fiberglass exterior doors c/w handle & deadbolt

EXTERIOR

- Vapour barrier house wrap
- "Nova Flash" envelope sealant on windows to prevent leaks
- Maintenance free exteriors with a combination of vinyl siding and aluminum around front windows & doors
- 30-year asphalt shingle
- Synthetic roof underlayment 100% of roof ice and dam rubberized membrane eaves and valley
- Eavestrough: 5" aluminum, surface draining down spouts, colour to match soffits & facia

PLUMBING & HEATING

PLUMBING

- 3-piece basement bathroom rough-in
- Individual shut-off valves and separate hot and cold manifolds
- Hot water tank as per Schedule A
- Two outside taps
- Waterline at fridge location

HEATING

- · High efficient furnace with pleated media filter
- Bathrooms wall fans & dryer vented to the exterior
- Programmable thermostat
- · Central ventilation exhaust fan
- All ducts power vacuumed prior to occupancy
- · All bathroom fans located on walls and vented through side walls where applicable
- Basic HRV system

FAUCETS AND FIXTURES

- Drop-in kitchen sink, double compartment stainless steel c/w standard single lever faucet
- Low flow aerators on all faucets and showerheads to reduce water consumption
- Standard white toilets and white china basins with faucet & mechanical waste
- Main Bathroom: One-piece tub shower combo unit with standard single lever faucet
- Main floor ½ bath vanity

ELECTRICAL & LIGHTING

ELECTRICAL

- 100-amp service
- · 220 volt wired to dryer and range
- Flat light switches
- Hardwired combination smoke and carbon monoxide detectors
- All bedroom and floor level circuits are Arc Fault protected per code w/tamper proof plugs throughout
- 2 exterior weather-proof outlets

- Rough-in central vac
- 1 telephone, 2 cable outlets
- · Soffit outlet switch for Christmas lights

LIGHT FIXTURES

- \$1.50/sq.ft lighting allowance
- 4 ~5" flush mounted pot lights

INSULATION & DRYWALL

- Spray foam insulated rim joists for greater air and vapour seal
- R12 fiberglass batt insulation basement frost wall
- R20 fiberglass batt insulation in wall cavity main & second floor
- R40 blown in, loose fill blown-in insulation attic
- ½" Drywall throughout
- 1/2" Ceiling board, textured
- Rounded drywall corners

CABINETRY & COUNTERTOPS

- Choice of flat panel oak, maple or hickory
- · Kitchen island with extended eating bar
- Square edge, laminate countertops in the kitchen and bathrooms
- 1 set of pot and pan drawers
- Built-in cabinet pantry

PAINTING

- Wall paint 1 coat primer, 2 finish coats latex paint in eggshell finish
- Trim paint 2 coats latex paint in semi-gloss finish
- Painted interior doors & bifolds

INTERIOR FINISHING & HARDWARE

INTERIOR FINISHING

- 6'-8" high, hollow core interior doors
- 4" flat baseboard, 3" flat window and door casing, paint grade MDF
- Appliance allowance \$5,000 includes GST
- Flooring allowance as per Schedule A

INTERIOR RAILING

• See Schedule A

MIRRORS, SHELVING AND SHOWER DOORS

- · All bathrooms included glass rectangular mirror
- Linen closet and pantry include 4 rows of white wire shelving
- Sliding, 5mm clear glass shower doors

LANDSCAPING OUTDOOR LIVING

- 18' x 18' min. gravel rear parking pad (with units that do not have garages)
- Rear 10'x10' pressure treated deck or as per plan size
- Front porch: pressure treated wood with metal railing as per plan

WARRANTIES

- Surveys, taxes, utilities, insurance and real property report to date of possession included
- 1-year service warranty on workmanship and materials
- 2-year warranty on delivery and distribution systems
- 5-year warranty on building envelope
- 10-year warranty on structural



DISCLAIMER: Falcon Homes Ltd. reserves the right to make modifications and/or substitutions to building designs & specifications without notice should they be necessary. Some features and options may not be available in some homes, which is dependent upon the design. All elevations, floor plans, room sizes, and square footage are based on conceptual design drawings and may vary.

PLEASE NOTE: Due to the volatile nature of material availability at this time, quoted prices and stock availability are subject to change without notice.











